



SAFETY DATA SHEET BELZONA® 3121 (MR7) BASE

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BELZONA® 3121 (MR7) BASE
Product number SN2846

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses An emergency repair and weatherproofing system for sealing all types of roof surfaces against atmospheric attack even during adverse weather conditions. Designed for instant weatherproofing at all times of year. For industrial use only.

Uses advised against The product should not be used for purposes other than those recommended in the appropriate Instructions For Use (IFU) leaflet.

1.3. Details of the supplier of the safety data sheet

Supplier Belzona Polymerics Limited
 Claro Road, Harrogate
 HG1 4DS
 United Kingdom
 +44 1423 567641
 sds@belzona.com

Manufacturer Belzona Polymerics Limited
 Claro Road, Harrogate
 HG1 4DS
 United Kingdom
 +44 1423 567641
 sds@belzona.com

1.4. Emergency telephone number

Emergency telephone VelocityEHS: +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)


Physical hazards Not Classified

Health hazards Skin Irrit. 2 - H315 Eye Irrit. 2 - H319 Skin Sens. 1 - H317

Environmental hazards Aquatic Chronic 2 - H411

Reference The full text for all hazard statements is displayed in Section 16.

2.2. Label elements

BELZONA® 3121 (MR7) BASE**Hazard pictograms****Signal word**

Warning

Hazard statements

H315 Causes skin irritation.
 H317 May cause an allergic skin reaction.
 H319 Causes serious eye irritation.
 H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

P273 Avoid release to the environment.
 P280 Wear protective gloves, protective clothing and eye protection.
 P302+P352 IF ON SKIN: Wash with plenty of water.
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P310 Immediately call a POISON CENTRE or doctor.
 P501 Dispose of contents/ container in accordance with national regulations.

Supplemental label information

Warning! Hazardous respirable droplets may be formed when sprayed. Do not breathe spray or mist.

Contains

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE, 4-NONYLPHENOL, Branched

2.3. Other hazards

Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product.

SECTION 3: Composition/information on ingredients**3.2. Mixtures**

BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE	10-30%
CAS number: 1675-54-3	EC number: 216-823-5
Classification	
Skin Irrit. 2 - H315	
Eye Irrit. 2 - H319	
Skin Sens. 1 - H317	
Aquatic Chronic 2 - H411	
HYDROCARBONS, C9, AROMATICS	5-10%
CAS number: —	EC number: 918-668-5
Classification	
Flam. Liq. 3 - H226	
STOT SE 3 - H335, H336	
Asp. Tox. 1 - H304	
Aquatic Chronic 2 - H411	

BELZONA® 3121 (MR7) BASE

4-NONYLPHENOL, Branched	< 3%
CAS number: 84852-15-3	EC number: 284-325-5
M factor (Acute) = 10	M factor (Chronic) = 10
Classification Acute Tox. 4 - H302 Skin Corr. 1B - H314 Eye Dam. 1 - H318 Repr. 2 - H361fd Aquatic Acute 1 - H400 Aquatic Chronic 1 - H410	

The full text for all hazard statements is displayed in Section 16.

Composition comments This mixture contains \geq 1% Titanium Dioxide (CAS 13463-67-7). The Annex VI classification of Titanium Dioxide does not apply to this mixture according to its Note 10.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information	In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
Inhalation	Remove to fresh air. Keep the patient warm and at rest. Give nothing by mouth.
Ingestion	If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with plenty of water. Do NOT induce vomiting.
Skin contact	Remove contaminated clothing. Wash skin thoroughly with soap and water or use a proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation persists, seek medical attention.
Eye contact	Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15 minutes, holding the eyelids apart, and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

General information	Contains a substance/a group of substances which may be toxic to reproduction.
Skin contact	Prolonged or repeated contact with the skin or mucous membrane may result in irritant symptoms such as redness, blistering or dermatitis. Onset of symptoms may be delayed. May cause an allergic skin reaction.
Eye contact	Irritating to eyes.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use: sand, alcohol resistant foam, carbon dioxide, chemical powder, or water fog for larger fires.
Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion products In a fire, hazardous decomposition products such as smoke, carbon monoxide and carbon dioxide may be produced.

BELZONA® 3121 (MR7) BASE

5.3. Advice for firefighters

Protective actions during firefighting

Fire will produce dense black smoke containing hazardous products of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not allow run-off from fire fighting to enter drains or watercourses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions

Exclude non-essential personnel. Keep up-wind of spill to avoid breathing vapours. Do not get on skin or in eyes.

6.2. Environmental precautions

Environmental precautions

Prevent spills from entering drains or sewers. If the product enters drains or sewers in large quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place into a suitable labelled container. Clean surfaces down with a water and detergent mixture. Do not allow spilled product or the associated washings to enter surface water drains or watercourses.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see section 13. For information on National regulating agencies refer to Section 16.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep the container tightly closed when not in use. Vapours may collect in the container headspace during transit or prolonged storage. Do not breathe vapour when opening the container. Where possible open containers and mix components in a well ventilated place away from the application area. Exclude non-essential personnel. Minimise the number of employees exposed and the duration of their exposure. Do not get on skin or in eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Always keep in containers made of the same material as the supply container. Ensure emergency equipment (for fires, spills, leaks, etc.) is readily available. FIRE/EXPLOSION This product is combustible. Exclude sources of heat, sparks and open flame. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards.

Advice on general occupational hygiene

Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing and shoes should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

7.2. Conditions for safe storage, including any incompatibilities

BELZONA® 3121 (MR7) BASE

Storage precautions

Observe the label precautions. Store between 5 °C and 30 °C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Have appropriate fire extinguishers available in and near the storage area. ENVIRONMENTAL STORAGE PRECAUTIONS Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes, especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and banded to contain any spillages.

7.3. Specific end use(s)

Specific end use(s)

Application by brush. Mix with Solidifier component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Occupational exposure limits

HYDROCARBONS, C9, AROMATICS

Long-term exposure limit (8-hour TWA): SUP 100 mg/m³

Ingredient comments

OEL's are taken from the current version of EH40 except those that are marked 'SUP' which are assigned by the supplier of the substance.

BIS-[4-(2,3-EPOXI)PHENYL]PROPANE (CAS: 1675-54-3)

DNEL

Workers - Dermal; Short term systemic effects: 8.3 mg/kg/day
 Workers - Inhalation; Short term systemic effects: 12.3 mg/m³
 Workers - Dermal; Long term systemic effects: 8.3 mg/kg/day
 Workers - Inhalation; Long term systemic effects: 12.3 mg/m³
 General population - Dermal; Short term systemic effects: 3.6 mg/kg/day
 General population - Inhalation; Short term systemic effects: 0.75 mg/m³
 General population - Oral; Short term systemic effects: 0.75 mg/kg/day
 General population - Dermal; Long term systemic effects: 3.6 mg/kg/day
 General population - Inhalation; Long term systemic effects: 0.75 mg/m³
 General population - Oral; Long term systemic effects: 0.75 mg/kg/day

PNEC

Fresh water; 0.003 mg/l
 Sediment (Freshwater); 0.5 mg/kg
 marine water; 0.0003 mg/l
 Sediment (Marinewater); 0.5 mg/kg
 Intermittent release; 0.013 mg/l
 STP; 10 mg/l
 Sediment; 0.05 mg/kg

HYDROCARBONS, C9, AROMATICS

DNEL

Workers - Inhalation; Long term systemic effects: 150 mg/m³
 Workers - Dermal; Long term systemic effects: 25 mg/kg/day
 Consumer - Inhalation; Long term systemic effects: 32 mg/m³
 Consumer - Dermal; Long term systemic effects: 11 mg/kg/day
 Consumer - Oral; Long term systemic effects: 11 mg/kg/day

4-NONYLPHENOL, Branched (CAS: 84852-15-3)

BELZONA® 3121 (MR7) BASE

DNEL	Workers - Inhalation; Long term systemic effects: 0.5 mg/m ³
	Workers - Inhalation; Short term systemic effects: 1 mg/m ³
	Workers - Dermal; Long term systemic effects: 7.5 mg/kg/day
	Workers - Dermal; Short term systemic effects: 15 mg/kg/day
	Consumer - Inhalation; Long term systemic effects: 0.4 mg/m ³
	Consumer - Inhalation; Short term systemic effects: 0.8 mg/m ³
	Consumer - Dermal; Long term systemic effects: 3.8 mg/kg/day
	Consumer - Dermal; Short term systemic effects: 7.6 mg/kg/day
	Consumer - Oral; Long term systemic effects: 0.08 mg/kg/day
Consumer - Oral; Short term systemic effects: 0.4 mg/kg/day	
PNEC	Fresh water; 0.000614 mg/l
	Sediment (Freshwater); 4.62 mg/kg
	marine water; 0.000527 mg/l
	Sediment (Marinewater); 1.23 mg/kg
	Intermittent release; 0.00017 mg/l
	STP; 9.5 mg/l
	Soil; 2.3 mg/kg

8.2. Exposure controls

Appropriate engineering controls

Use in well ventilated areas or provide adequate mechanical ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of vapours below the relevant occupational exposure limits, suitable respiratory protective equipment should be worn (see 'Respiratory protection' below).

Eye/face protection

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection. During subsequent machining, grinding, abrasion or removal of this product appropriate eye protection should be selected according to the type of tools or equipment used.

Hand protection

Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred. **SPECIFIC RECOMMENDATIONS** Wear protective gloves made of the following material: Nitrile rubber. **STANDARD APPLICATIONS** Medium-heavy weight gauntlet type gloves that provide wrist protection are suitable.

Other skin and body protection

STANDARD APPLICATIONS Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. **APPLICATION OF SMALL QUANTITIES** Cotton overalls are normally suitable.

BELZONA® 3121 (MR7) BASE

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. It is essential that the concentration of the contaminant(s) in the application environment does not exceed the applicable Occupational Exposure Limit(s) (OELs) multiplied by the Assigned Protection Factor (APF) quoted for the respiratory protective equipment selected. Respiratory protection is not normally required, but the hazards of the Solidifier component should be considered for mixing and application purposes. Respiratory protection is not normally required but it may be required when this product is used in confined spaces or where adequate ventilation cannot be achieved. Where necessary, it is recommended that respiratory protective equipment that complies with EN 136 (full face mask) or EN 140 (half face mask) should be worn in combination with an organic/inorganic vapours, acid gases and ammonia cartridge (ABEK1). Where the application environment is likely to be contaminated by significant concentrations of dust then the appropriate particulate prefilter (N-, R- or, P-series) should be worn in combination with the above. It is essential that the facepiece is correctly fitted and the filter is changed in accordance with the manufacturer's instructions. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance	Thixotropic liquid.
Colour	Grey.
Odour	Hydrocarbons.
Odour threshold	Not applicable.
pH	Not applicable.
Melting point	Not applicable.
Initial boiling point and range	*>155°C/>311°F @ 760 mm Hg
Flash point	75°C/167°F Closed cup.
Evaporation rate	No information available.
Flammability (solid, gas)	Not applicable.
Upper/lower flammability or explosive limits	Not applicable.
Vapour pressure	< 0.43 kPa @ 20°C/68°F
Vapour density	Not available.
Relative density	1.58-1.68 @ 20°C/68°F
Solubility(ies)	Immiscible with water.
Partition coefficient	Not available.
Auto-ignition temperature	*355°C/671°F
Decomposition Temperature	Not available.
Viscosity	Not available.
Explosive properties	Not applicable.
Oxidising properties	Not applicable.

BELZONA® 3121 (MR7) BASE

Comments *Quoted value relates to solvent content.

9.2. Other information

Other information This section contains typical values for Health, Safety and Environmental guidance only and is not intended to represent a technical specification for the product.

Volatile organic compound This product contains a maximum VOC content of 305 g/litre (determined by ASTM D2369-10/D).

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable under recommended storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

Possibility of hazardous reactions No hazardous reactions expected when stored and handled as recommended.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Keep away from strongly alkaline and strongly acidic materials to prevent the possibility of exothermic reaction.

10.6. Hazardous decomposition products

Hazardous decomposition products Does not decompose when used and stored as recommended.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Irritating to skin.

Serious eye damage/irritation

Serious eye damage/irritation Irritating to eyes.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on the properties of the epoxy constituent(s) and considering toxicological data on similar preparations, this preparation may be a skin sensitizer. Repeated skin contact may lead to sensitisation with possibly cross-sensitisation to other epoxies.

BELZONA® 3121 (MR7) BASE

Germ cell mutagenicity

Genotoxicity - in vitro Based on available data the classification criteria are not met.

Genotoxicity - in vivo Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Not listed.

NTP carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Contains a substance/a group of substances which may damage fertility.

Reproductive toxicity - development Contains a substance/a group of substances which may be toxic to reproduction.

Specific target organ toxicity - single exposure

STOT - single exposure Not classified as a specific target organ toxicant after a single exposure.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Not classified as a specific target organ toxicant after repeated exposure.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

Route of exposure Skin and/or eye contact

Medical considerations Skin contact constitutes a pronounced hazard. Persons with a history of skin sensitisation problems should only be employed in processes in which this product is used under appropriate medical supervision.

Toxicological information on ingredients.

BIS-[4-(2,3-EPOXI)PHENYL]PROPANE

Toxicological effects @@@Repeated skin contact may lead to sensitization with possibly cross-sensitization to other epoxies.@@@ @@@In rare cases, low molecular weight liquid epoxy resins can cause an allergic respiratory reaction like asthma, based on limited human information. The evidence available is not however, considered to fall within the classification criteria as laid out within the OSHA Hazard Communication Standard nor the Controlled Products Regulations.@@@

4-NONYLPHENOL, Branched

Toxicological effects @@@In a testicular toxicity study nonylphenol exposure had effects on some reproductive organs weights and sperm characteristic but did not influence the mating behaviour, fertility or developed fetuses.@@@ @@@In a teratogenicity study a dose level of 300 mg/kg caused clear maternal toxic effects based on increased mortality, reduced body weight gain and food consumption. With regard to the embryo-fetal development a NOAEL of >= 300 mg/kg was found.@@@

Acute toxicity - oral

Acute toxicity oral (LD₅₀ mg/kg) 1,412.0

BELZONA® 3121 (MR7) BASE

Species Rat

SECTION 12: Ecological information

Ecotoxicity There is no data on the product itself. The following information is provided on the basis of the individual component data available.

12.1. Toxicity

Toxicity Based on the individual component data, the product is expected to have experimental LC50/EC50/IC50 values between 1 and 10 mg/l in most sensitive species.

Ecological information on ingredients.**BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE**

Toxicity Based on the epoxy resin content, this product is expected to have experimental LC50/EC50/IC50 values between 1 and 10 mg/l in most sensitive species.

4-NONYLPHENOL, Branched**Acute aquatic toxicity**

LE(C)₅₀ 0.01 < L(E)C50 ≤ 0.1

M factor (Acute) 10

Chronic aquatic toxicity

NOEC 0.001 < NOEC ≤ 0.01

Degradability Non-rapidly degradable

M factor (Chronic) 10

12.2. Persistence and degradability

Persistence and degradability Based on the individual component data, the product is not expected to be rapidly biodegradable according to OECD/EC guidelines.

Ecological information on ingredients.**BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE**

Persistence and degradability Based on the epoxy resin content, this product is not expected to be rapidly biodegradable according to OECD/EC guidelines.

12.3. Bioaccumulative potential

Bioaccumulative potential Based on the individual component data, the product is expected to bioaccumulate.

Partition coefficient Not available.

Ecological information on ingredients.**BIS-[4-(2,3-EPOXIPROPOXI)PHENYL]PROPANE**

Bioaccumulative potential Based on the epoxy resin content, this product Log octanol/water partition coefficient (Log Kow) is expected to be greater than 4.0.

12.4. Mobility in soil

Mobility There is no data available on the product itself.

12.5. Results of PBT and vPvB assessment

BELZONA® 3121 (MR7) BASE

Results of PBT and vPvB assessment Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product.

12.6. Other adverse effects

Other adverse effects None known.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. In addition, hazardous chemical wastes should be disposed of in accordance with the Hazardous Waste Regulations. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16. COMPONENT DISPOSAL TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be re-used or recycled. UNREACTED PRODUCT and empty uncleaned containers should be disposed of as hazardous chemical waste. REACTED PRODUCT, contaminated mixing boards, spatulas, applicators, brushes, nominally empty containers and mixing bowls- once fully cured- should be disposed of as non-hazardous waste.

Waste class List of Waste (LoW) code: 08 01 11*. *Hazardous waste pursuant to Directive 91/689/EEC. The LoW code quoted in this section is a general entry. LoW codes should be assigned based on the end use of the product. Where a more specific code is available it should be used in preference to the code given above. Where in doubt refer to the List of Wastes (2000/532/EC Commission Decision), your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

SECTION 14: Transport information

General Labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

14.1. UN number

UN No. (ADR/RID) 3082

UN No. (IMDG) 3082

UN No. (ICAO) 3082

14.2. UN proper shipping name

Proper shipping name (ADR/RID) Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

Proper shipping name (IMDG) Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

Proper shipping name (ICAO) Environmentally hazardous substance, liquid, n.o.s. (containing Epoxy resin mixture)

14.3. Transport hazard class(es)

ADR/RID class 9

IMDG class 9

ICAO class/division 9

BELZONA® 3121 (MR7) BASE

14.4. Packing group

ADR/RID packing group III

IMDG packing group III

ICAO packing group III

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

Yes. Labelling requirements will vary with hazardous net quantity. Please refer to the current transport regulations.

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Annex II of MARPOL 73/78 Not carried in bulk.

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations Relevant EU provisions transposed through retained EU law.

EU legislation

Regulation (EC) No 1272/2008 of the European Parliament and of the Council of 16 December 2008 on classification, labelling and packaging of substances and mixtures (as amended).
Regulation (EC) No 1907/2006 of the European Parliament and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restriction of chemicals (REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information

The information contained within this safety data sheet does not constitute the users own assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of technical performance or suitability for particular applications.

Key literature references and sources for data

Provision and Use of Personal Protective Equipment Regulations 1992 (SI 1992: 2932).
PPG18: Control of Spillages and fire fighting run-off. HSG53 The selection, use and maintenance of respiratory protective equipment, as amended. HSG97 A step by step guide to COSHH assessment. Working with ADR: An introduction to the carriage of dangerous goods by road. UK ENVIRONMENTAL REGULATING AGENCIES: England and Wales- Environment Agency; Scotland- Scottish Environment Protection Agency (SEPA); Northern Ireland- Environment and Heritage Service.

Training advice

For further information please contact your supplier, Belzona consultant or Belzona direct.

BELZONA® 3121 (MR7) BASE

Revision comments	REVISION. This safety data sheet has been revised in the following Section(s): 1, 2, 3, 4, 5, 6, 7, 8, 11, 12, 15, Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent to you.
Revision date	03/08/2022
Revision	4.4
SDS status	English. Approved.
Hazard statements in full	H226 Flammable liquid and vapour. H302 Harmful if swallowed. H304 May be fatal if swallowed and enters airways. H314 Causes severe skin burns and eye damage. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H318 Causes serious eye damage. H319 Causes serious eye irritation. H335 May cause respiratory irritation. H336 May cause drowsiness or dizziness. H361fd Suspected of damaging fertility. Suspected of damaging the unborn child. H400 Very toxic to aquatic life. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects.