3D-Printed Mesh for Live Leak Sealing Applications





Used in conjunction with Belzona 1212, the 3D-printed mesh facilitates live leak sealing of small holes on straight pipes operating at pressures of up to ~10Bar.

Belzona 9621 moulds over various pipe diameters and eliminates the need for a prefabricated bypass plate.

Belzona 1212, supplied separately, is a fast-curing surface-tolerant epoxy material. It demonstrates outstanding adhesion and mechanical properties offering lasting protection.

	Mixing ratio (Base : Solidifier)	14.5 : 1 by weight* *Refer to IFU for thickness greater than 38 mm (11/2 inch)			
	Working life	30 minutes at 25°C (77°F) 3 years			
∀ ⊢	Shelf life				
DA	Compressive strength	102.9 MPa (14,930 psi) at 20°C (68°F) cure and test			
NICAL	Hardness	Shore D: 89.5	Barcol: 40		
	Adhesion (pull-off) *cohesive failure of substrate	Mild steel: 26.8 MPa (3,880 psi)	Concrete: 6.8 MPa (980 psi)*		
CH	Shear strength	45.4 MPa (6,590 psi) at 20°C (68°F) cure and test 4360 cm³ (266 in³) / 6.95 kg at 12-100 mm (0.5-4 in)			
H	Volume capacity				
	Tensile strength	44.2 MPa (6,410 psi) at 20°C (68°F) cure and test			
	Adhesion (tensile shear)	Mild steel: 24.6 MPa (3,570 psi)	Stainless steel: 20.0 MPa (2,900 psi)		

TIMES	Temperature	15°C (60°F)	20°C (68°F)	30°C (86°F)	25°C (77°F)
CURE	Cure times	48 hours	24 hours	12 hours	5 hours

^{*}Please consult the Product Specification Sheet (PSS) and Instructions for Use (IFU) for the latest technical data.



SIMPLE APPLICATION



FAST CURING



QUICK RETURN TO SERVICE



PRESSURE RESISTANT



Step-by-step application:



1. Roughen surface



2. Cut hole in the reinforcement sheet



3. Dry-fit sheet to mesh



4. Mix Belzona 1212



5. Wet-out pipe



6. Wet-out mesh



7. Wet-out sheet



8. Position mesh and sheet




9. Wrap and smooth



10. Fit bolt and tighten



11. Completed application





Watch on BelzonaTV

For more information, please contact your local Belzona representative:

QUALITY PRODUCTS - TECHNICAL SUPPORT

Belzona products are manufactured under an ISO 9001 Registered Quality Management System.

Belzona has a global distribution network of over 140 Distributors operating in 120 countries. Local support is provided by a trained Technical Consultant who will diagnose the problem, recommend the solution and provide 24-hour, on-site application supervision and advice.