

SAFETY DATA SHEET BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

Product number SN2863, SN2864

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses Thick film grade elastomeric repair compound for resurfacing applications. For industrial use

only.

appropriate Instructions For Use (IFU) leaflet.

1.3. Details of the supplier of the safety data sheet

Supplier Belzona Polymerics Limited

Claro Road, Harrogate

HG1 4DS United Kingdom +44 1423 567641 sds@belzona.com

Manufacturer Belzona Polymerics Limited

Claro Road, Harrogate

HG1 4DS United Kingdom +44 1423 567641 sds@belzona.com

1.4. Emergency telephone number

Emergency telephone VelocityEHS: +1 813-248-0585

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Classification (SI 2019 No. 720)

Physical hazards Not Classified

Health hazards Not Classified

Environmental hazards Not Classified

2.2. Label elements

Hazard statements NC Not Classified

Precautionary statements P280 Wear protective clothing and gloves.

2.3. Other hazards

Based on information received from our suppliers no PBT or vPvB substances are intentionally added to this product. This product does not contain components considered to have endocrine disrupting properties at ≥ 0.1%.

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

SECTION 3: Composition/information on ingredients

3.2. Mixtures

levels of disclosure.

SECTION 4: First aid measures

4.1. Description of first aid measures

General information In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything

by mouth to an unconscious person.

Inhalation Remove to fresh air. Keep the patient warm and at rest. Give nothing by mouth.

Ingestion If accidentally swallowed obtain immediate medical attention. Keep at rest. Rinse mouth with

plenty of water. Do NOT induce vomiting.

Skin contact Remove contaminated clothing. Wash skin thoroughly with soap and water or use a

proprietary skin cleaner. Do NOT use solvents or thinners. If irritation or inflammation

persists, seek medical attention.

Eye contact Contact lenses should be removed. Irrigate copiously with clean, fresh water for at least 15

minutes, holding the eyelids apart, and seek medical advice.

4.2. Most important symptoms and effects, both acute and delayed

General information No specific health hazards known.

4.3. Indication of any immediate medical attention and special treatment needed

Notes for the doctor None.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media Use: sand, alcohol resistant foam, carbon dioxide, chemical powder, or water fog for larger

fires.

Do NOT use water jet.

5.2. Special hazards arising from the substance or mixture

Hazardous combustion

products

In a fire, hazardous decomposition products such as smoke, carbon monoxide and carbon

dioxide may be produced.

5.3. Advice for firefighters

Protective actions during

firefighting

Fire will produce dense black smoke containing hazardous products of combustion. Exposure to decomposition products may be a hazard to health. Appropriate self-contained breathing apparatus may be required. Cool closed containers exposed to fire with water spray. Do not

allow run-off from fire fighting to enter drains or watercourses.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

get on skin or in eyes.

6.2. Environmental precautions

Environmental precautions Prevent product entering drains or sewers. If the product enters drains or sewers in large

quantities, the local Water Company should be contacted immediately; in the case of contamination of streams, rivers or lakes, the appropriate National regulating agency.

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

6.3. Methods and material for containment and cleaning up

Methods for cleaning up

Contain and collect spillages with non-combustible absorbent materials e.g. sand, earth, vermiculite, diatomaceous earth and place into a suitable labelled container. Clean surfaces down with a water and detergent mixture. Do not allow spilled product or the associated washings to enter surface water drains or watercourses.

6.4. Reference to other sections

Reference to other sections

For personal protection, see Section 8. For waste disposal, see section 13. For information on National regulating agencies refer to Section 16.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Usage precautions

Keep the container tightly closed when not in use. Vapours may collect in the container headspace during transit or prolonged storage. Do not breathe vapour when opening the container. Where possible open containers and mix components in a well ventilated place away from the application area. Do not get on skin or in eyes. Smoking, eating and drinking should be prohibited in areas of storage and use. For personal protection see Section 8. Exclude non-essential personnel. Minimise the number of employees exposed and the duration of their exposure. Always keep in containers made of the same material as the supply container. Good housekeeping standards and regular safe removal of waste materials will minimise the risks of spontaneous combustion and other fire hazards. FIRE/EXPLOSION This product is combustible. Exclude sources of heat, sparks and open flame. SPECIAL Should heating be required to revert any partial solidification, it should be ensured that the temperature is controlled to the lowest possible level, in any case it should not exceed 50°C. Indirect heating methods should be used. All electrical equipment should be protected to the appropriate standard. Do not breathe vapours/mists.

Advice on general occupational hygiene

Wash at the end of each work shift and before eating, smoking and using the toilet. Ensure eye wash facilities (fountain, bottle, vials, etc.) are readily available. Do not put contaminated articles or equipment e.g. spatulas, applicators, brushes, cloths etc., into pockets. Where necessary, contaminated work clothing and shoes should be removed to prevent cross contamination of surfaces and the risk of inadvertent skin contact and ingestion.

7.2. Conditions for safe storage, including any incompatibilities

Storage precautions

Observe the label precautions. Store between 5 °C and 30 °C unless otherwise stated in a dry, well ventilated place away from sources of heat, ignition and direct sunlight. No smoking. Prevent unauthorised access. Store separately from oxidising agents and strongly alkaline and strongly acidic materials. ENVIRONMENTAL STORAGE PRECAUTIONS Spillage, incorrect storage of chemicals or waste materials or unsuitable disposal activities can result in pollutants seeping through the soil, causing serious harm to groundwater- which is a vital source of drinking water. All wastes, especially liquid wastes, must be securely stored on site in designated areas that are isolated from surface drains and bunded to contain any spillages.

7.3. Specific end use(s)

Specific end use(s)

Application by plastic applicator or spatula provided. Application by brush. Mix with Belzona® 2100 Base component before use. Please refer to the relevant Belzona® Instructions For Use for further information.

SECTION 8: Exposure controls/Personal protection

8.1. Control parameters

Ingredient comments

No exposure limits known for ingredient(s).

8.2. Exposure controls

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

Appropriate engineering controls

Use in well ventilated areas or provide adequate mechanical ventilation. Where reasonably practicable this should be achieved by the use of local exhaust ventilation and good general extraction. Where these controls are not sufficient to maintain concentrations of particulates and/or vapours to an acceptable level, suitable respiratory protective equipment should be worn (see 'Respiratory protection' below).

Eye/face protection

It is recommended that eye protection, for example safety spectacles or goggles are worn at all times during the handling and use of this material. Eye protection should be selected in accordance with EN 166 Personal eye protection.

Hand protection

Hand protection should be selected in accordance with EN 374 Protective gloves against chemicals. The breakthrough time of the gloves selected should exceed the expected use period. Where this is not possible gloves should be changed in good time, and in any case before the breakthrough time is exceeded. If any doubt exists, advice should be sought from glove suppliers on appropriate types. Barrier creams may help to protect exposed areas of skin but are not substitutes for full physical protection. They should not be applied once exposure has occurred. SPECIFIC RECOMMENDATIONS Wear protective gloves made of the following material: Nitrile rubber. Medium-heavy weight gauntlet type gloves that provide wrist protection are suitable.

Other skin and body protection

STANDARD APPLICATIONS Synthetic polyethylene coveralls such as the Tyvek PRO-TECH® or equivalent coveralls manufactured to EN 13034 Type 6, Protective clothing against liquid chemicals. Grossly contaminated clothing should be removed and the skin washed with soap and water or a proprietary skin cleaner. APPLICATION OF SMALL QUANTITIES Cotton overalls are normally suitable.

Respiratory protection

Respiratory protection complying with an approved standard should be worn if a risk assessment indicates inhalation of contaminants is possible. Respirator selection must be based on exposure levels, the hazards of the product and the safe working limits of the selected respirator. It is essential that the concentration of the contaminant(s) in the application environment does not exceed the applicable Occupational Exposure Limit(s) (OELs) multiplied by the Assigned Protection Factor (APF) quoted for the respiratory protective equipment selected. Respiratory protection is not normally required, but the hazards of the Base component should be considered for mixing and application purposes. Respiratory protection is not normally required but it may be required when this product is used in confined spaces or where adequate ventilation cannot be achieved. Where necessary, it is recommended that respiratory protective equipment that complies with EN 136 (full face mask) or EN 140 (half face mask) should be worn in combination with an organic/inorganic vapours, acid gases and ammonia cartridge (ABEK1). Where the application environment is likely to be contaminated by significant concentrations of dust then the appropriate particulate prefilter (N-, R- or, P-series) should be worn in combination with the above. It is essential that the facepiece is correctly fitted and the filter is changed in accordance with the manufacturer's instructions. In confined or poorly-ventilated spaces, a supplied-air respirator must be worn.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance Liquid.

ColourRed. Black.OdourOdourless.

Odour threshold Not applicable.

pH Not applicable.Melting point Not available.

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

Initial boiling point and range >135°C/>275°F @ 760 mm Hg

Flash point >140°C/>284°F Closed cup.

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or

explosive limits

Not applicable.

Vapour pressure Not available.

Vapour density Not available.

Relative density 1.07 - 1.17 @ 20°C

Solubility(ies) Not available.

Partition coefficient Not available.

Auto-ignition temperature Not applicable.

Decomposition Temperature >300°C/>572°F

Viscosity

Not applicable.

Explosive properties

Not applicable.

Oxidising properties

Not applicable.

9.2. Other information

Other information This section contains typical values for Health, Safety and Environmental guidance only and is

not intended to represent a technical specification for the product.

SECTION 10: Stability and reactivity

10.1. Reactivity

Reactivity There are no known reactivity hazards associated with this product.

10.2. Chemical stability

Stability Stable under recommended storage and handling conditions (see Section 7).

10.3. Possibility of hazardous reactions

Possibility of hazardous

reactions

No hazardous reactions expected when stored and handled as recommended.

10.4. Conditions to avoid

Conditions to avoid There are no known conditions that are likely to result in a hazardous situation.

10.5. Incompatible materials

Materials to avoid Keep away from oxidising agents and strongly alkaline and strongly acidic materials to

prevent the possibility of exothermic reaction.

10.6. Hazardous decomposition products

Hazardous decomposition Does not decompose when used and stored as recommended.

products

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity - oral

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

Notes (oral LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - dermal

Notes (dermal LD₅₀) Based on available data the classification criteria are not met.

Acute toxicity - inhalation

Notes (inhalation LC₅₀) Based on available data the classification criteria are not met.

Skin corrosion/irritation

Animal data Based on available data the classification criteria are not met.

Serious eye damage/irritation

Serious eye damage/irritation Based on available data the classification criteria are not met.

Respiratory sensitisation

Respiratory sensitisation Based on available data the classification criteria are not met.

Skin sensitisation

Skin sensitisation Based on available data the classification criteria are not met.

Germ cell mutagenicity

Genotoxicity - in vitro

Based on available data the classification criteria are not met.

Genotoxicity - in vivo

Based on available data the classification criteria are not met.

Carcinogenicity

Carcinogenicity Based on available data the classification criteria are not met.

IARC carcinogenicity Not listed.

NTP carcinogenicity Not listed.

Reproductive toxicity

Reproductive toxicity - fertility Based on available data the classification criteria are not met.

Reproductive toxicity -

development

Based on available data the classification criteria are not met.

Specific target organ toxicity - single exposure

STOT - single exposure Based on available data the classification criteria are not met.

Specific target organ toxicity - repeated exposure

STOT - repeated exposure Based on available data the classification criteria are not met.

Aspiration hazard

Aspiration hazard Based on available data the classification criteria are not met.

General information This product does not contain components considered to have endocrine disrupting properties

at ≥ 0.1%.

SECTION 12: Ecological information

Ecotoxicity There is no data on the product itself. The following information is provided on the basis of the

individual component data available.

12.1. Toxicity

ToxicityBased on the individual component data, the products LC50/EC50/IC50 are expected to be

greater than 100 mg/l in most sensitive species.

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

12.2. Persistence and degradability

Persistence and degradability Based on the individual component data, the product is not expected to be rapidly

biodegradable according to OECD/EC guidelines.

12.3. Bioaccumulative potential

Bioaccumulative potential This product is not expected to present an environmental hazard under current legislation.

Partition coefficient Not available.

12.4. Mobility in soil

Mobility There is no data available on the product itself.

12.5. Results of PBT and vPvB assessment

Results of PBT and vPvB

assessment

Based on information received from our suppliers no PBT or vPvB substances are

intentionally added to this product.

12.6. Other adverse effects

Other adverse effects None known. This product does not contain components considered to have endocrine

disrupting properties at ≥ 0.1%.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal methods

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Controlled wastes include non-hazardous industrial and hazardous chemical wastes. All controlled wastes should be disposed of in accordance with regulations made under the Control of Pollution Act and the Environmental Protection Act. When in doubt, using information provided in this safety data sheet, advice should be obtained from the National regulating agency whether the Hazardous Waste Regulations apply. Refer to information sources listed in Section 16. COMPONENT DISPOSAL TRANSIT PACKAGING: shrink or stretch wrap, boxes and fittings that have not been contaminated with product should be reused or recycled. UNREACTED PRODUCT and empty uncleaned containers should be disposed of as non-hazardous waste. REACTED PRODUCT, contaminated mixing boards, spatulas, applicators, brushes, nominally empty containers and mixing bowls- once fully cured- should be disposed of as non-hazardous waste.

Waste class

List of Waste (LoW) code: 08 01 12. The LoW code quoted in this section is a general entry. LoW codes should be assigned based on the end use of the product. Where a more specific code is available it should be used in preference to the code given above. Where in doubt refer to the List of Wastes, your local licensed waste contractor or the National regulating agency. Refer to information sources listed in Section 16.

SECTION 14: Transport information

General

Not classified for transport under current National and International Regulations. Labelling and packaging requirements may vary with pack and load size. Please refer to the current transport regulations. Transport within user's premises: always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of accident or spillage.

14.1. UN number

Not applicable.

14.2. UN proper shipping name

Not applicable.

14.3. Transport hazard class(es)

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

Not applicable.

14.4. Packing group

Not applicable.

14.5. Environmental hazards

Environmentally hazardous substance/marine pollutant

No

14.6. Special precautions for user

Not applicable.

14.7. Transport in bulk according to Annex II of MARPOL and the IBC Code

Transport in bulk according to Not carried in bulk.

Annex II of MARPOL 73/78

and the IBC Code

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

National regulations The provisions of the Health and Safety at Work Act and the Control of Substances

Hazardous to Health Regulations with amendments apply to the use of this product at work.

Relevant EU provisions transposed through retained EU law.

EU legislation Regulation (EC) No 1272/2008 of the European Parliment and of the Council of 16 December

2008 on classification, labelling and packaging of substances and mixtures (as amended). Regulation (EC) No 1907/2006 of the European Parliment and of the Council of 18 December 2006 concerning the Registration, Evaluation, Authorisation and Restrition of chemicals

(REACH) (as amended).

15.2. Chemical safety assessment

No chemical safety assessment has been carried out.

SECTION 16: Other information

General information The information contained within this safety data sheet does not constitute the users own

assessment of workplace risks as required by other health and safety legislation. As the specific conditions of use of the product are outside the supplier's control, the user is responsible for ensuring that the requirements of relevant National legislation are complied with. The information contained within this safety data sheet is based on the present state of knowledge and current national legislation. It provides guidance on health, safety and environmental aspects of the product and should not be construed as any guarantee of

technical performance or suitability for particular applications.

Key literature references and

sources for data

Provision and Use of Personal Protective Equipment Regulations 1992 (SI 1992: 2932). PPG18: Control of Spillages and fire fighting run-off. HSG53 The selection, use and maintenance of respiratory protective equipment, as amended. HSG97 A step by step guide to COSHH assessment. UK ENVIRONMENTAL REGULATING AGENCIES: England and Wales- Environment Agency; Scotland- Scottish Environment Protection Agency (SEPA);

Northern Ireland- Environment and Heritage Service.

Classification procedures according to SI 2019 No. 720

Where there is no test data available for the mixture, the classification has been determined based on the individual component hazard data in accordance with EC 1272/2008.

Training advice For further information please contact your supplier, Belzona consultant or Belzona direct.

BELZONA® 2121 (D&A HI-COAT ELASTOMER) SOLIDIFIER

REVISION. This safety data sheet has been revised in the following Section(s): 1, 11, 12, 15,

Please observe the REVISION DATE. Should you be reading a safety data sheet that is more than 24 months old or have concerns over its validity, please contact your local Belzona consultant or Belzona direct (sds@belzona.com) and the most current information will be sent

to you.

Revision date 02/02/2023

Revision 1.4

SDS number 40970

SDS status English. Approved.